


## OT 250/220-240/24 P (NEW)

CV Power supplies 24 V



### Product family features

- DC mode functionality
- Type of protection: IP66 and IP67
- Surge protection: up to 4 kV (L-N) / 6 kV (L/N-PE)
- Wide operating temperature range: -30...+55 °C
- Lifetime: up to 50,000 h (temperature at max.  $t_c$ )

### Product family benefits

- Large range of products from 20 W to 250 W
- Installation in very cold and hot environments
- Very stable output power
- High electrical reversible short-circuit, overload, overtemperature protection
- Smart Power Supply: boosting power to turn on cold LEDs
- Independent installation possible

## Areas of application

- Facades, public squares, cruise ships
- Signage
- Suitable for indoor and outdoor installations

## Technical data


### Electrical data

|  |                     |
|--|---------------------|
| Nominal input voltage                    | 220...240 V         |
| Mains frequency                          | 0...60 Hz           |
| Input voltage AC                         | 198...264 V         |
| Input voltage DC                         | 176...250 V         |
| Total harmonic distortion                | < 15 %              |
| Power factor $\lambda$                   | 0.95                |
| Efficiency in full-load                  | 92 % <sup>1)</sup>  |
| Device power loss                        | 21.7 W              |
| Inrush current                           | 75 A                |
| Max. ECG no. on circuit breaker 10 A (B) | 3                   |
| Max. ECG no. on circuit breaker 16 A (B) | 8                   |
| Surge capability (L/N-Ground)            | 6 kV                |
| Surge capability (L-N)                   | 4 kV                |
| Nominal output voltage                   | 24.2 V              |
| Nominal output power                     | 250 W               |
| Maximum output power                     | 250 W <sup>2)</sup> |
| Galvanic isolation                       | SELV                |

1) at 230 V, 50 Hz

2) at steady state

## Dimensions & weight



|   |                     |
|---|---------------------|
| <b>Length</b>                               | 265.0 mm            |
| <b>Width</b>                                | 68.0 mm             |
| <b>Height</b>                               | 40.0 mm             |
| <b>Mounting hole spacing, length</b>        | 250.0 mm            |
| <b>Cable cross-section, input side</b>      | 1.0 mm <sup>2</sup> |
| <b>Cable cross-section, output side</b>     | 1.5 mm <sup>2</sup> |
| <b>Wire preparation length, input side</b>  | 90 mm               |
| <b>Wire preparation length, output side</b> | 90 mm               |
| <b>Product weight</b>                       | 1340.00 g           |

## Colors & materials

|                        |       |
|------------------------|-------|
| <b>Casing material</b> | Metal |
|------------------------|-------|

## Temperatures & operating conditions

|   |                        |
|---|------------------------|
| <b>Ambient temperature range</b>                | -30...+55 °C           |
| <b>Maximum temperature at tc test point</b>     | 85 °C                  |
| <b>Max.housing temperature in case of fault</b> | 110 °C                 |
| <b>Temperature range at storage</b>             | -40...+85 °C           |
| <b>Permitted rel. humidity during operation</b> | 5...85 % <sup>1)</sup> |

1) Maximum 56 days/year at 85 %

## Lifespan

|              |         |
|--------------|---------|
| ECG lifetime | 50000 h |
|--------------|---------|

## Additional product data

|                 |               |
|-----------------|---------------|
| Predecessor EAN | 4008321981721 |
|-----------------|---------------|

## Capabilities

|  |        |
|--|--------|
| Dimmable                               | No     |
| Suitable for fixtures with prot. class | I      |
| Type of connection, output side        | Cables |
| Number of channels                     | 1      |
| Overheating protection                 | Yes    |
| Overload protection                    | Yes    |
| Short-circuit protection               | Yes    |
| Intended for no-load operation         | No     |
| No-load proof                          | Yes    |

## Certificates & standards

|                                  |  |
|----------------------------------|--|
| <b>Approval marks – approval</b> | ENEC / RCM / CCC / EAC / CE  |
| <b>Standards</b>                 | Acc. to EN 61347-1 / Acc. to EN 61347-2-13 / Acc. to EN 55015 / Acc. to EN 61547 / Acc. to EN 61000-3-2 / Acc. to EN 61000-3-3 / Acc. to EN 60598-1 / Acc. to EN 62384 |
| <b>Type of protection</b>        | IP66/IP67  |

## Logistical data

|                       |             |
|-----------------------|-------------|
| <b>Commodity code</b> | 85044083900 |
|-----------------------|-------------|

## Environmental information

| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |               |
|---|---------------|
| <b>Date of Declaration</b>  | 04-06-2024    |
| <b>Primary Article Identifier</b>                                     | 4052899546028 |
| <b>Declaration No. in SCIP database</b>                               | In work       |
| <b>SCIP_STATUS</b>  | In work       |
| <b>SCIP_ID</b>  |               |

## Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

## Download Data

| File                       |            |  |
|----------------------------|------------|--|
| Brochures                  | PDF        | ▶ OPTOTRONIC constant-voltage LED power supplies and controls (EN) |
| Product Datasheet          | PDF        | ▶ Datasheet OT 250/220-240/24 P                                    |
| Certificates               | PDF        | ▶ CCC Certificate No. 2018011002043871                             |
| Certificates               | PDF        | ▶ OT 24 P CB 4163267 01 101023                                     |
| Certificates               | PDF        | ▶ ENEC Certificate No. U6 18 01 84117 048                          |
| CAD data 3-dim             | Compressed | ▶ OT 250 220-240 24 P- 3D stp file                                 |
| Declarations of conformity | PDF        | ▶ Attestation of Conformity No. N8A 18 01 84117 054                |
| Declarations of conformity | PDF        | ▶ Attestation of Conformity No. E8A 18 01 84117 049                |
| Declarations of conformity | PDF        | ▶ OT 24V P DIMP CE 3537796 09 080823                               |
| User instruction           | PDF        | ▶ OPTOTRONIC® LED Power Supply                                     |



## Logistical Data

| Product code  | Product description | Packaging unit (Pieces/Unit)     | Dimensions (length x width x height) | Volume                | Gross weight |
|---------------|---------------------|----------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899546028 | OT 250/220-240/24 P | Shipping carton box<br>10 Pieces | 459 x 344 x 144 mm                   | 22.74 dm <sup>3</sup> | 1475.20 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.