


## EM FIT 75/220-240/1600 CS L G2 (NEW)

Linear / Area Constant Current – Non dimmable



### Product family features

- Line frequency: 50 Hz | 60 Hz
- Supply voltage: 220...240 V
- Lifetime: up to 100,000 h (temperature at  $T_c = 65^\circ\text{C}$ , max. 10 % failure rate)
- Type of protection: IP20
- Non-isolated drivers
- SELV driver

### Product family benefits

- Small, slim white metal housing (W)30 x (H)21 mm
- Flexible current setting (DIPswitch – 4 currents)
- High efficiency and reliability
- Enhanced safety due to overload, overtemperature, short-circuit protection
- High light quality due to low ripple current
- Long lasting and high reliability

### Areas of application

- Linear and area lighting
- Linear lighting for office, school and public areas
- Suitable for luminaires of protection class I

## Technical data

### Electrical data

Nominal input voltage	220...240 V
Mains frequency	50/60 Hz
Input voltage AC	198...264 V
Input voltage DC	not relevant
Total harmonic distortion	< 20 % <sup>1)</sup>
Power factor $\lambda$	0.91C...0.98 <sup>2)</sup>
Efficiency in full-load	89 % <sup>3)</sup>
Device power loss	9.7 W <sup>4)</sup>
Networked standby power	not relevant
Inrush current	60 A <sup>5)</sup>
Max. ECG no. on circuit breaker 10 A (B)	7
Max. ECG no. on circuit breaker 16 A (B)	12
Max. ECG no. on circuit breaker 25 A (B)	18
Surge capability (L-N)	1 kV
Surge capability (L/N-Ground)	2 kV <sup>6)</sup>
Protective conductor current	0.5 mA
Nominal output voltage	27...51 V / 27...48 V <sup>7)</sup>
U-OUT (working voltage)	< 60 V
Nominal output current	1300 mA / 1400 mA / 1500 mA / 1600 mA <sup>8)</sup>
Output current tolerance	±7.5 %
Output ripple current (100 Hz)	< 10 %
Output PSTLM	≤1
Output SVM	≤0.4
Nominal output power	35.1...76.8 W <sup>9)</sup>
Maximum output power	76.8 W

1) At full load

2) Full load at 220...240 V<sub>AC</sub>/50 Hz

3) at 230 V, 50 Hz

4) At 230 V

5)  $t_{width} = 190 \mu s$  typical (measured at 50 %  $I_{peak}$ )


6) L/N – PE acc to EN 61547 Cluase 5.7

7) At 1300/1400/1500 mA output current / At 1600 mA output current


8) ±7.5%

9) Partial load

## Typical Power Factor v Load




## Operating Window




Typical Power factor vs load of EM FIT 75W 1600 CS L G2

Typical Operating window of EM FIT 75W 1600 CS L G2

## Typical THD v Load




## Typical Efficiency v Load 230 V 50 Hz



Typical THD vs load of EM FIT 60W 1200 CS L G2

Typical Efficiency vs load of EM FIT 75W 1600 CS L G2

## Dimensions & weight



Product weight	210.00 g
Length	280.0 mm
Width	30.0 mm
Height	21.0 mm
Mounting hole spacing, length	270.0 mm
Mounting hole spacing, width	not relevant mm
Cable cross-section, input side	0.5...1.5 mm <sup>2</sup> / 0.75...1.5 mm <sup>2</sup> <sup>1)</sup>
Cable cross-section, output side	0.5...1.5 mm <sup>2</sup> / 0.75...1.5 mm <sup>2</sup> <sup>1)</sup>
Wire preparation length, input side	7...8 mm
Wire preparation length, output side	7...8 mm

1) Solid or flexible leads

## Colors & materials

Casing material	Metal
Product color	White

## Temperatures & operating conditions

Ambient temperature range	-25...+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Temperature range at storage	-40...85 °C
Permitted rel. humidity during operation	5...90 % <sup>1)</sup>

1) Non-condensing

## Lifespan

ECG lifetime	50000 h / 100000 h <sup>1)</sup>
--------------	----------------------------------

1) At maximum  $T_c = 75^\circ\text{C}$  / 10% failure rate / At maximum  $T_c = 65^\circ\text{C}$  / 10% failure rate

## Additional product data

Encapsulated	No
Predecessor EAN	4062172220033

## Capabilities

Programming interface	Dipswitch
Dimmable	No
Constant lumen function	No
Max. cable length to lamp/LED module	2.0 m <sup>1)</sup>
Suitable for fixtures with prot. class	I
Type of connection, input side	Terminal
Type of connection, output side	Terminal
Number of channels	1
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
Intended for no-load operation	No
No-load proof	Yes

1) Output wires must be routed as close as possible to each other

## Programming

Programming device	DIPswitch
Tuner4TRONIC	No
Tuner4TRONIC Field App	No
Box programming	No

## Certificates & standards

Approval marks – approval	CE / ENEC / CCC / RCM / TISI / BIS
Standards	Acc. to IEC 61347-1 / Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to IEC 61000-3-2 / Acc. to IEC 61547 / Acc. to IEC 61000-4-5
Type of protection	IP20

## Logistical data

Commodity code	85044083900
----------------	-------------

## Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-10-2024
Primary Article Identifier	6977078992657
Declaration No. in SCIP database	In work
SCIP_STATUS	In work
SCIP_ID	

### Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.



### Additional product information

- Hot plug-in or secondary switching of LEDs is not permitted and may cause a very high current to the LEDs.
- Indication that the lamp control gear relies upon the luminaire enclosure for protection against accidental contact with live parts.

### Download Data

File		
Certificates	PDF	► EM FIT CS L G2 CB DE1 68840B1 080724
Certificates	PDF	► EM FIT 75 CS L G2 CCC 2024171002005361 010724
Certificates	PDF	► EM FIT CS L G2 ENEC 40058248 080724
CAD data 3-dim	Compressed	► EM FIT 75 L G2 CAD3PDF 181024
CAD data	Compressed	► EM FIT 75 L G2 IGS 181024
CAD data	Compressed	► EM FIT 75 L G2 STEP 181024
Mandatory Publications	PDF	► EM FIT CS L G2 CE 4534711 00 160724
User instruction	PDF	► UI EM FIT CS L G2

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
6977078992657	EM FIT 75/220-240/1600 CS L G2	Shipping carton box 20 Pieces	300 x 156 x 96 mm	4.49 dm³	216.26 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.