The trusted value of OSRAM Digital Systems continues with Inventronics Global – where experience meets innovation.

OT FIT 50/220-240/300 D L (PHASE OUT)

OPTOTRONIC FIT D L | Linear / Area Constant Current - Non dimmable



Product family features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile scope of application due to output power range of up to 50 W
- Supply voltage: 220...240 V
- Available with output current range: up to 350 mA
- Non-isolated drivers

Product family benefits

- Small housing design
- Fixed current
- Lifetime: up to 100,000 h (temperature at T_c = 65 °C, max. 10 % failure rate)
- High quality of light thanks to low output ripple current
- High efficiency
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection



Areas of application

- Linear lighting for office, education, industry, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for installation in emergency lighting systems according to EN 60598-2-22
- Suitable for luminaires of protection class I

Technical data

Electrical data

Nominal input voltage	220240 V
Mains frequency	0/50/60 Hz
Input voltage AC	198264 V ¹⁾
Input voltage DC	176276 V
Nominal input current at 230 V	0.27 A
Total harmonic distortion	< 20 %
Power factor λ	> 0.95
Efficiency in full-load	90 % ²⁾
Device power loss	5.0 W ³⁾
Networked standby power	not relevant
Inrush current	not relevant
Max. ECG no. on circuit breaker 10 A (B)	35
Max. ECG no. on circuit breaker 16 A (B)	56
Max. ECG no. on circuit breaker 25 A (B)	89
Surge capability (L-N)	1 kV
Surge capability (L/N-Ground)	2 kV
Protective conductor current	0.31 mA
Nominal output voltage	54175 V
U-OUT (working voltage)	< 250 V
Nominal output current	300 mA ⁴⁾
Default output current	300 mA
Output current tolerance	±10 %
Output ripple current (100 Hz)	≤ 5 %
Output PSTLM	≤1
Output SVM	≤0.4
Nominal output power	16.252.5 W
Maximum output power	52.5 W

¹⁾ Permitted voltage range


²⁾ at 230 V, 50 Hz


³⁾ Maximum

^{4) ±5%}

Typical Power Factor v Load

Typical THD v Load







OT FIT 50/220-240/D L Typical Power Factor vs. Load

Typical lout v Rset LEDset2 mode

OT FIT 50/220-240/D L Typical THD Vs Load

Typical Efficiency v Load 230 V 50 Hz







OT FIT 50/220-240/D L Typical lout vs Rset (LEDset2 mode)

OT FIT 50/220-240/D L Typical Efficiency vs. Load (230 V / 50 Hz)

Dimensions & weight





Product weight	125.00 g
Length	210.0 mm
Width	30.0 mm
Height	21.0 mm
Mounting hole spacing, length	200.0 mm
Mounting hole spacing, width	not relevant mm
Cable cross-section, input side	0.51.5 mm ²
Cable cross-section, output side	0.51.5 mm²
Wire preparation length, input side	8.59.5 mm
Wire preparation length, output side	8.59.5 mm

Colors & materials

Casing material	Metal

Temperatures & operating conditions

Ambient temperature range	-15+50 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Temperature range at storage	-2585 °C
Permitted rel. humidity during operation	585 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %



Lifespan

ECG lifetime	50000 h / 100000 h ¹⁾

1) At maximum $T_c = 75^{\circ}$ C / 10% failure rate / At $T_c = 65^{\circ}$ C / 10% failure rate

Capabilities

Dimmable	No
Constant lumen function	No
Max. cable length to lamp/LED module	2.0 m ¹⁾
Suitable for fixtures with prot. class	1
Suitable for emergency lighting	Yes
Type of connection, input side	Push terminal
Type of connection, output side	Push terminal
Number of channels	1
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
Intended for no-load operation	No
No-load proof	Yes

¹⁾ Output wires must be routed as close as possible to each other



Programming

Programming device	not relevant

Certificates & standards

Approval marks – approval	CE / EL / VDE-ENEC / VDE-EMC / EAC / CCC / BIS / RCM			
Standards	EN 61347-1 / EN 61347-2-13 / EN 55015 / EN 61547 / EN 61000-3-2 / EN 62384 / EN 62386			
Type of protection	IP20			

Logistical data

Commodity code	85044083900

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration 12-02-2025			
Primary Article Identifier	4052899469884		
Declaration No. in SCIP database In work			
SCIP_STATUS	In work		
SCIP_ID			



Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.



Download Data

File		
Certificates	PDF	►OT ENEC 40038085 230824
CAD data 3-dim	Compressed	►OT FIT D L CAD3PDF 261119
CAD data 2-dim	Compressed	►OT FIT D L CAD2PDF 261119
CAD data	Compressed	►OT FIT D L IGS 261119
CAD data	Compressed	►OT FIT D L STEP 261119
Mandatory Publications	PDF	►OT FIT D L CE 4292770 04 160523
Mandatory Publications	PDF	►OT FIT D L UK DoC 4289774 01 140222



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899469884 OSRAM	OT FIT 50/220-240/300 D L	Shipping carton box 20 Pieces	234 x 161 x 101 mm	3.81 dm³	133.25 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.