

## OTi DALI 80/220-240/2A1 NFC L

OPTOTRONIC Intelligent – DALI NFC (SELV) | Linear constant current LED driver – Dimmable



### Product family features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile DALI window driver up to 50 W due to flexible output characteristic
- Supply voltage: 220...240 V
- Available with output current range: up to 1,400 mA
- Constant Lumen Output (CLO)
- Integrated customizable thermal management (Driver Guard)

### Product family benefits

- Fully programmable via software (DALI Interface, NFC)
- Advanced luminaire/driver data (power, energy, operating hours...) for analytics
- DALI-2 certified incl. Parts 251, 252, 253
- Lifetime: up to 100,000 h (temperature at  $T_c = 65^\circ\text{C}$ , max. 10 % failure rate)
- High-quality dimming of 1...100 % by amplitude dimming
- Higher quality of light thanks to < 3% output ripple current
- Very high efficiency
- Very low standby power consumption: < 0.15 W \*
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection

## Areas of application

- Linear lighting for office, education, industry, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for luminaires of protection class I


## Technical data

### Electrical data

Max. ECG no. on circuit breaker 10 A (B)	8
Max. ECG no. on circuit breaker 16 A (B)	13
Maximum output power	80 W
Nominal output current	600...2100 mA
Nominal output power	32...80 W
Nominal output voltage	20...54 V
Nominal input voltage	220...240 V
Input voltage AC	198...264 V
Input voltage DC	176...276 V
Device power loss	8.0 W
Efficiency in full-load	91 % <sup>1)</sup>
Inrush current	≤ 30 A
Networked standby power	≤ 0.19 W <sup>1)</sup>
Power factor λ	0.83C...0.99
Mains frequency	0/50/60 Hz
Surge capability (L-N)	1 kV
Surge capability (L/N-Ground)	2 kV
U-OUT (working voltage)	< 60 V
Current set	DALI / NFC / Programmable
Output current tolerance	±3 %
Output ripple current (100 Hz)	≤ 3 %
Total harmonic distortion	≤ 10 %
Default output current	600 mA

1) at 230 V, 50 Hz

## Dimensions & weight



Product weight	270.00 g
Length	360.0 mm
Height	21.0 mm
Width	30.0 mm
Cable cross-section, input side	0.5...1.5 mm <sup>2</sup>
Cable cross-section, output side	0.5...1.5 mm <sup>2</sup>
Mounting hole spacing, length	350.0 mm
Wire preparation length, input side	8.0...9.0 mm
Wire preparation length, output side	8.0...9.0 mm

## Colors & materials

Casing material	Metal
-----------------	-------

## Temperatures & operating conditions

Ambient temperature range	-25...+50 °C
Max.housing temperature in case of fault	110 °C
Maximum temperature at tc test point	75 °C
Permitted rel. humidity during operation	5...85 % <sup>1)</sup>
Temperature range at storage	-40...+85 °C

1) Maximum 56 days/year at 85 %

## Lifespan

ECG lifetime	100000 h / 50000 h
--------------	--------------------

## Additional product data

Encapsulated	No
--------------	----

## Capabilities

Max. cable length to lamp/LED module	2.0 m <sup>1)</sup>
Number of channels	1
Dimmable	Yes
Dimming interface	DALI-2 / Touch DIM / Touch DIM Sensor
Dimming method	Full analogue dimming
Dimming range	1...100 %
Overload protection	Automatic reversible
Overheating protection	Automatic reversible
Short-circuit protection	Automatic reversible
Suitable for emergency lighting	Yes
Suitable for fixtures with prot. class	I
Type of connection, input side	Push terminal
Type of connection, output side	Push terminal
No-load proof	Yes
Programming interface	DALI, NFC

1) Output wires must be routed as close as possible to each other

## Programmable features

<b>DALI-2 Luminaire Data</b>	Yes
------------------------------	-----

## Certificates & standards

<b>Type of protection</b>	IP20
<b>Standards</b>	Acc. to IEC 61347-1 / Acc. to IEC 61347-2-13 / Acc. to IEC 62384 / Acc. to IEC 62386 / Acc. to IEC 61000-3-2 / Acc. to IEC 61000-3-3 / Acc. to IEC 61347
<b>Approval marks – approval</b>	CE / EL / VDE-ENEC / EAC / CCC / BIS / RCM

## Logistical data

<b>Commodity code</b>	85044083900
-----------------------	-------------

## Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

## Download Data

File		
Certificates	PDF	▶ OT ENEC 40038447 270224
CAD data 2-dim	Compressed	▶ OTI DALI 80 NFC L CAD2PDF 271021
CAD data 3-dim	Compressed	▶ OTI DALI 80 NFC L CAD3PDF 271021
CAD data	Compressed	▶ OTI DALI 80 NFC L IGS 271021
CAD data	Compressed	▶ OTI DALI 80 NFC L STEP 271021
Mandatory Publications	PDF	▶ OTI DALI NFC L CE 4159050 06 160523
Mandatory Publications	PDF	▶ OTI DALI NFC L UK DoC 4281121 03 060923
User instruction	PDF	▶ OPTOTRONIC LED Power Supply



## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172238656	OTi DALI 80/220-240/2A1 NFC L	Shipping carton box 20 Pieces	385 x 160 x 100 mm	6.16 dm <sup>3</sup>	174.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit

## Accessories Optional

Product description	Accessory name	Accessory code
OTi DALI 80/220-240/2A1 NFC L	PRH101 -USB	▶ 6977078996938
OTi DALI 80/220-240/2A1 NFC L	CPR30 -USB	▶ 6977078996945

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.