The trusted value of OSRAM Digital Systems continues with Inventronics Global – where experience meets innovation.

OTi DALI 35/220-240/1A0 NFC L

OPTOTRONIC Intelligent - DALI NFC (SELV) | Linear constant current LED driver - Dimmable



Product family features

- Line frequency: 0 Hz | 50 Hz | 60 Hz
- Versatile DALI window driver up to 80 W due to flexible output characteristic
- Supply voltage: 220...240 V
- Available with output current range: up to 2,100 mA
- Constant Lumen Output (CLO)
- Integrated customizable thermal management (Driver Guard)

Product family benefits

- Fully programmable via software (DALI Interface, NFC)
- Advanced luminaire/driver data (power, energy, operating hours...) for analytics
- DALI-2 certified incl. Parts 251, 252, 253
- Lifetime: up to 100,000 h (temperature at T = 65 °C, max. 10 % failure rate)
- High-quality dimming of 1...100 % by amplitude dimming
- Higher quality of light thanks to < 3% output ripple current
- Very high efficiency
- Very low standby power consumption: < 0.15 W *
- Fulfill safety requirement due to overload, overtemperature, Hot Plug protection



Areas of application

- Linear lighting for office, education, industry, storage areas and retail
- Installation in emergency lighting systems according to IEC 61347-2-13, appendix J
- Suitable for luminaires of protection class I




Technical data

Electrical data

Nominal input voltage	220240 V
Mains frequency	0/50/60 Hz
Input voltage AC	198264 V
Input voltage DC	176276 V
Total harmonic distortion	≤ 10 %
Power factor λ	0.61C0.98
Efficiency in full-load	89 % ¹⁾
Device power loss	3.0 W
Networked standby power	<0.15 W ¹⁾
Inrush current	≤ 20 A
Max. ECG no. on circuit breaker 10 A (B)	14
Max. ECG no. on circuit breaker 16 A (B)	24
Surge capability (L-N)	1 kV
Surge capability (L/N-Ground)	2 kV
Protective conductor current	0.21 mA
Nominal output voltage	1554 V
U-OUT (working voltage)	< 60 V
Nominal output current	2001050 mA
Default output current	350 mA
Output current tolerance	±3 %
Output ripple current (100 Hz)	≤ 3 %
Output PSTLM	≤1
Output SVM	≤0.4
Nominal output power	437 W
Maximum output power	37 W

¹⁾ at 230 V, 50 Hz

Dimensions & weight



Product weight	209.00 g
Length	280.0 mm
Width	30.0 mm
Height	21.0 mm
Mounting hole spacing, length	270.0 mm
Cable cross-section, input side	0.51.5 mm²
Cable cross-section, output side	0.51.5 mm ²
Wire preparation length, input side	8.09.0 mm
Wire preparation length, output side	8.09.0 mm

Colors & materials

Casing material	Metal
Odding material	Wictar

Temperatures & operating conditions

Ambient temperature range	-25+60 °C
Maximum temperature at tc test point	75 °C
Max.housing temperature in case of fault	110 °C
Temperature range at storage	-40+85 °C
Permitted rel. humidity during operation	585 % ¹⁾

¹⁾ Maximum 56 days/year at 85 %

ECG lifetime	100000 h / 50000 h

Additional product data

Encansulated	No
Elicapsulated	140

Capabilities

Programming interface	DALI, NFC
Control interface	DALI
Dimmable	Yes
Dimming interface	DALI-2 / Corridor / Touch DIM / Touch DIM Sensor
Dimming range	1100 %
Dimming method	Full analogue dimming
DALI-2 Diagnostic Data	Yes
DALI-2 Energy Data	Yes
Constant lumen function	Programmable
Max. cable length to lamp/LED module	2.0 m ¹⁾
Suitable for fixtures with prot. class	1
Suitable for emergency lighting	Yes
Type of connection, input side	Push terminal
Type of connection, output side	Push terminal
Number of channels	1
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
Intended for no-load operation	No
No-load proof	Yes
•	

¹⁾ Output wires must be routed as close as possible to each other



Programming

Programming device	DALI magic / NFC Scanner
Tuner4TRONIC	Yes
Tuner4TRONIC Field App	Yes
Box programming	Yes

Programmable features

DALI Settings	Yes
DALI-2 Luminaire Data	Yes
TouchDIM + Sensor	Yes
Corridor Functionality	Yes
Dim to Dark	Yes
Soft Switch Off	Yes
Tuning Factor	Yes
Driver Guard	Yes
Emergency Mode	Yes

Certificates & standards

Approval marks – approval	CE / EL / VDE-ENEC / EAC / CCC / BIS / RCM
Standards	IEC 61347-1 / IEC 61347-2-13 / IEC 62384 / IEC 62386 / IEC 61000-3-2 / IEC 61000-3-3 / IEC 61347
Type of protection	IP20

Logistical data

Commodity code	85044083900

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	12-09-2025		
Primary Article Identifier	4062172074964 6937186106605		
Declaration No. in SCIP database	In work		
SCIP_STATUS	In work		
SCIP_ID			



Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

Download Data

File		
Certificates	PDF	►OTI DALI 35 NFC L EAT AM31194 191219
Certificates	PDF	►OTI DALI 35 NFC L INO AM31194 191219
Certificates	PDF	►OT ENEC 40038447 270224
CAD data 2-dim	Compressed	►OTI DALI NFC L CAD2PDF 030220
CAD data 3-dim	Compressed	►OTI DALI NFC L CAD3PDF 030220
CAD data	Compressed	►OTI DALI NFC L IGS 030220
CAD data	Compressed	►OTI DALI NFC L STEP 030220
Mandatory Publications	PDF	►OTI DALI NFC L CE 4159050 09 200125
Mandatory Publications	PDF	►OTI DALI NFC L UK DoC 4281121 03 060923
User instruction	PDF	►UI OTI DALI NFC L



Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172074964 OSRAM	OTi DALI 35/220- 240/1A0 NFC L	Shipping carton box 20 Pieces	303 x 159 x 105 mm	5.06 dm³	215.35 g
6937186106605 INVENTRONICS	OTi DALI 35/220- 240/1A0 NFC L	Shipping carton box 20 Pieces	303 x 159 x 105 mm	5.06 dm³	216.15 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit

Accessories Optional

Product description	Accessory name	Accessory code
OTi DALI 35/220-240/1A0 NFC L	PRH101 -USB	▶6977078996938
OTi DALI 35/220-240/1A0 NFC L	PRH101 -USB	▶6937186112354
OTi DALI 35/220-240/1A0 NFC L	CPR30+	▶6977078996945
OTi DALI 35/220-240/1A0 NFC L	CPR30+	► 6937186112378

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.