
The trusted value of OSRAM Digital Systems continues with Inventronics Global – where experience meets innovation.

# IT DALI 60/220-240/1A4 CS

# ICUTRONIC DALI CS | Constant Current Compact - Dimmable



### Product family features

Supply voltage: 220...240 VLine voltage: 198...264 V

- Line frequency: 0 Hz | 50 Hz | 60 Hz

- Lifetime: up to 50,000 h (temperature at max. t )

- Type of protection: IP20

### Product family benefits

- Safety ensured by Inventronics (SELV)
- DALI-2 certified
- High flexibility due to eight different output currents
- Touch DIM application: easy to control via pushbutton or sensor
- Easy to use in corridors and restrooms because of three-level Corridor function
- Higher quality of light thanks to low output ripple current
- Small housing for flexible luminaire designs
- Housing from 80% recycled plastic





Specifications are subject to changes without notice.

© 2025, Inventronics GmbH. All rights reserved. Inventronics is a licensee of the OSRAM brand. OSRAM is a trademark of ams OSRAM

www.inventronicsglobal.com



# Product - technical datasheet

# Areas of application

- Offices
- Shops
- Hospitality
- Panels, spotlight, downlight, and other indoor LED luminaires
- Suitable for indoor SELV equivalent installations
- Suitable for luminaires of protection classes I and II
- Installation in emergency lighting systems according to IEC 61347-2-3, appendix J

#### Technical data

### **Electrical data**

Nominal input voltage	220240 V
Mains frequency	0/50/60 Hz
Input voltage AC	198264 V <sup>1)</sup>
Input voltage DC	176276 V
Nominal input current at 230 V	0.317 A <sup>2)</sup>
Total harmonic distortion	< 10 % <sup>3)</sup>
Power factor λ	0.980.99
Efficiency in full-load	91 % <sup>4)</sup>
Device power loss	7.1 W <sup>5)</sup>
Networked standby power	<0.50 W <sup>4)</sup>
Inrush current	20 A <sup>6)</sup>
Max. ECG no. on circuit breaker 10 A (B)	25
Max. ECG no. on circuit breaker 16 A (B)	40
Surge capability (L-N)	1 kV
Surge capability (L/N-Ground)	2 kV
Protective conductor current	<0.7 mA
Nominal output voltage	2754 V <sup>7)</sup>
U-OUT (working voltage)	60 V
Nominal output current	700 mA / 800 mA / 900 mA / 1000 mA / 1050 mA / 1200 mA / 1300 mA / 1400 mA
Minimum output current	14 mA
Default output current	1400 mA
Output current tolerance	±5 %
Output ripple current (100 Hz)	< 5 % <sup>8)</sup>
Output PSTLM	≤1
Output SVM	≤0.4
Nominal output power	16.858.8 W
Maximum output power	58.8 W
Galvanic isolation primary/secondary	SELV
Galvanic isolation DALI/mains	Basic
Galvanic isolation DALI/output	SELV

<sup>1)</sup> Permitted voltage range

<sup>2)</sup> At full load, steady operation

<sup>3)</sup> At full load, 220...240 V, 50 Hz / see graphs

<sup>4)</sup> at 230 V, 50 Hz


<sup>5)</sup> Maximum / Full load, 230 Vac, 50Hz / 60Hz


<sup>6)</sup> t<sub>width</sub> = 100 μs (measured at 50 % I<sub>peak</sub>) 7) Maximum 60 V

<sup>8)</sup> Ripple average at 100 Hz

# Typical Power Factor v Load

# **Operating Window**







IT DALI 60 CS Typical Power Factor vs. Load

IT DALI 60 CS Operating window

## Typical THD v Load

Typical Efficiency v Load 230 V 50 Hz







IT DALI 60 CS Typical THD Vs Load

IT DALI 60 CS Typical Efficiency vs. Load

## **Dimensions & weight**





Product weight	155.00 g
Length	103.0 mm
Width	67.0 mm
Height	29.5 mm
Mounting hole spacing, length	94.0 mm
Mounting hole spacing, width	58.0 mm
Cable cross-section, input side	0.51.5 mm <sup>2</sup> / 0.751.5 mm <sup>2</sup> <sup>1)</sup>
Cable cross-section, output side	0.51.5 mm² / 0.751.5 mm² <sup>1)</sup>
Wire preparation length, input side	78 mm
Wire preparation length, output side	78 mm
Cable/wire length, output side	2000 mm

<sup>1)</sup> Build in/ Independent

# Colors & materials

Casing material	Plastic
Product color	White

## Temperatures & operating conditions

Ambient temperature range	-20+50 °C
Maximum temperature at tc test point	80 °C <sup>1)</sup>
Max.housing temperature in case of fault	110 °C
Temperature range at storage	-40+85 °C
Permitted rel. humidity during operation	585 % <sup>2)</sup>
Permitted relative humidity at storage	585 %

<sup>1)</sup> Maximum at the Tc-point

<sup>2)</sup> Maximum 56 days/year at 85 %



## Lifespan

ECG lifetime	50000 h <sup>1)</sup>

1) At maximum  $T_c = 80^{\circ}$ C / 10% failure rate

# Additional product data

Encapsulated	No
--------------	----

## Capabilities

Programming interface	Dipswitch
Control interface	DALI-2, Touch DIM, Corridor
Dimmable	Yes
Dimming interface	DALI-2 / Touch DIM / Corridor
Dimming range	1100 % 1)
Dimming method	Amplitude Modulation
Constant lumen function	No
Max. cable length to lamp/LED module	2.0 m <sup>2)</sup>
Suitable for fixtures with prot. class	1/11
Suitable for emergency lighting	Yes
Type of connection, input side	Push terminal
Type of connection, output side	Push terminal
Suitable for through-wiring	Yes with optional cable clamp
Number of channels	1
Overheating protection	Automatic reversible
Overload protection	Automatic reversible
Short-circuit protection	Automatic reversible
Intended for no-load operation	No
No-load proof	Yes

<sup>1)</sup> For maximum nominal output current

<sup>2)</sup> Output wires must be routed as close as possible to each other

## **Programming**

Programming device	DALI / DIPswitch
Tuner4TRONIC	Yes
Tuner4TRONIC Field App	No
Box programming	No

### **Programmable features**

DALI Settings	Yes
TouchDIM + Sensor	Yes
Corridor Functionality	Yes
Dim to Dark	No
Soft Switch Off	No
Tuning Factor	No
Configuration Lock	Yes
Driver Guard	No
Thermal Protection	Yes
Emergency Mode	Yes

### Certificates & standards

Approval marks – approval	CE / ENEC / EL / RCM / CCC / KC / BIS
Standards	IEC 61347-1 / IEC 61347-2-13 / EN 55015 / IEC 61547 / IEC 61000-3-2 / IEC 62384
Type of protection	IP20

## Logistical data

Commodity code	85044083900

### **Environmental information**

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)	
Date of Declaration	30-07-2025
Primary Article Identifier	4062172373982   6977078994071
Declaration No. in SCIP database	In work
SCIP_STATUS	In work
SCIP_ID	



## Product - technical datasheet

## Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.



# Product - technical datasheet

## **Download Data**

File		
Certificates	PDF	►IT DALI CS CB SG PSB LE 05577 240124
Certificates	PDF	►IT DALI CS CB SG PSB LE 05578 240124
Certificates	PDF	►IT DALI CS ENEC 64142225005704 U6 310124
CAD data 3-dim	Compressed	►IT DALI 60 CS CAD3PDF 241024
CAD data 2-dim	Compressed	►IT DALI 60 CS CAD2PDF 241024
CAD data	Compressed	►IT DALI 60 CS STEP 241024
Mandatory Publications	PDF	►IT DALI CS CE 4414207 05 240125
User instruction	PDF	►UI IT DALI 60 CS

#### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172373982 OSRAM	IT DALI 60/220-240/1A4 CS	Shipping carton box 20 Pieces	353 x 223 x 95 mm	7.48 dm³	170.50 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit

#### Data privacy

This Inventronics driver can be configured using the Tuner4TRONIC software. This requires registering on www.inventronicsglobal.com/ds and downloading theTuner4TRONIC software from the Internet. The Tuner4TRONIC software enables users to access and view the operational data of a luminaire or driver via the corresponding programming interfaces. A password key (Config Lock) must be set up in the driver via the Tuner4TRONIC software in order to control which users can access and view operational data. Follow the instructions for password setup. To grant an external person or company rights to access or view operational data, you can assign password keys. In this case, however, you are responsible for ensuring that the third party concerned takes notice of the information described here. However, Inventronics can read out operating data from devices for maintenance and service purposes even when a password key has been assigned. In individual cases, Inventronics will also use its access rights in order to optimize or improve driver hardware and driver functions. In accordance with data privacy principles, any user of operating data (luminaire manufacturers, third parties with access rights) must ensure that personal data (e.g. name, address, location IDs) are only merged with the prior written consent of the person (end user) concerned. The respective user of the operating data is responsible for providing evidence of consent.

#### **Accessories Optional**

Product description	Accessory name	Accessory code
IT DALI 60/220-240/1A4 CS	OT CABLE CLAMP B-STYLE	<b>►</b> 4052899077881
IT DALI 60/220-240/1A4 CS	OT CABLE CLAMP B-STYLE	▶6977770432147
IT DALI 60/220-240/1A4 CS	OT CABLE CLAMP B-STYLE TL	<b>4</b> 052899948051
IT DALI 60/220-240/1A4 CS	OT CABLE CLAMP B-STYLE TL	▶6977770432161

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.