DALI-2 SENSOR LS/PD O CI (NEW)

DALI-2 SENSOR LS/PD O CI | Sensors



Product family features

- Light and presence sensor for ceiling integration
- Presence detection via passive IR element
- Light sensor operating range: 5...2000 lx (measured at sensor)
- Detection height up to 4 meter
- Function indicator LED

Product family benefits

- Large motion detection range
- Simple and fast installation via wire springs
- DALI-2 certified
- DALI Bus powered (No mains connection necessary)
- Multiple sensors connectable to the same DALI line
- Shutter included to optimize sensor detection
- Integreatable in light- and building management systems supporting DALI-2 sensors

www.inventronicsglobal.com

Areas of application

- Open offices
- Indoor navigation
- Conference rooms
- Classrooms
- Storage and break areas
- Stairways
- Sanitary areas


Technical data


Electrical data

Required DALI current (typical)	8 mA
Peak DALI current	8 mA
System wattage	0.1 W

Specifications are subject to changes without notice.

Dimensions & weight





Mounting hole spacing, diagonal	68 mm
Product weight	120.00 g
Length	105.0 mm
Width	105.0 mm
Height	67.0 mm

Colors & materials

Product color	White

Temperatures & operating conditions

Ambient temperature range	-20+45 °C

product - technical datasheet

Capabilities

Operating range, light sensor	52000 lx
Dimming interface	DALI-2
Detection area	12 m²
Maximum installation height	4 m
Dimmable	No
Type of installation	Ceiling integration

product - technical datasheet

Certificates & standards			
Type of protection	IP20		
_ogistical data			
Commodity code	90318080000		
Environmental information			
	Regulation (EC) 1907/2006 (REACh)		
	Regulation (EC) 1907/2006 (REACh) 4052899630444		
Information according Art. 33 of EU			
Information according Art. 33 of EU Primary Article Identifier	4052899630444		
Information according Art. 33 of EU Primary Article Identifier Date of Declaration	4052899630444 24-12-2024		

Equipment / Accessories

- Optional: Surface mounting via QBM 220-240 LS/PD CM KIT

- Optional: IP54 with Surface mounting KIT

Download Data

File				
Mandatory Publications	PDF	DALI2 SENSOR LS PD CE 4419446 02 160823		
Mandatory Publications	latory Publications PDF DALI2 SENSOR UKDoC 4419451 02 180923			
User instruction	PDF	► DALI-2 Sensors LS PD O CI LS PD C CI		

Specifications are subject to changes without notice.

product - technical datasheet

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899630444	DALI-2 SENSOR LS/PD O CI	Shipping carton box 24 Pieces	525 x 390 x 215 mm	44.02 dm ³	264.17 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.