

Manufacturer: OSRAM GmbH Marcel-Breuer Str. 6 D-80807 München	Product: <b>OTi DALI 50/220-240/1A4 LT2 FAN</b> <b>( 4052899488182 )</b>	<b>OSRAM GmbH</b>
--	--	-------------------

**Important Note:**

All driver parameter data given in EL-Requirement datasheets reflect the drivers ex-factory state. The paramters are changeable via T4T configuration software.

Table 1

Values for load range	In in AC-operation (230V) / mA (trms)	In in AC-operation (240V) / mA (trms)	In in DC-operation (186V) / mA (trms)	In in DC-operation (216V) / mA (trms)	In in DC-operation (240V) / mA (trms)	In in DC-operation (260V) / mA (trms)
Umin, Imin	68,63	68,34	18,73	16,32	15,02	13,86
Umin, Imax	137,33	140,24	28,43	24,65	22,62	21,42
Umax, Imin	161,51	155,61	36,34	31,45	28,66	26,98
Umax, Imax	245,27	214,40	46,35	39,99	36,33	34,01
Open/Short Load	32,91	40,51	12,68	12,32	11,98	11,93

**Remarks:**

- 1.) This table shows the currents consumption of the driver at three different operating points (Pmax, Pmid, Pmin) for AC and DC operation.
- 2.) This table is intended for rough design decisions . It is not a replacement for individual functional measurements!