

Manufacturer: OSRAM GmbH Marcel-Breuer Str. 6 D-80807 München	Product: OT FIT 25/220...240/700 LT2 LP (4052899490697)	OSRAM GmbH
--	---	-------------------

Table 1

Values for load range	AC-operation				DC-Operation (For DALI Devices @ default DC Dim level e.g. 15%)			
	189VAC/50Hz Itrms_in (mA)	230VAC/50Hz Itrms_in (mA)	240VAC/50Hz Itrms_in (mA)	264VAC/50Hz Itrms_in (mA)	186VDC Itrms_in (mA)	216VDC Itrms_in (mA)	240VDC Itrms_in (mA)	260VDC Itrms_in (mA)
Min. Load /mA P_out= 8 W	not supported (110)	102	102	97	108	100	72	67
Mid. Load /mA P_out= 12,5 W	not supported (126)	113	111	110	124	112	104	98
Max. Load /mA P_out= 25 W	not supported (182)	156	152	143	182	160	145	135
Short/Open Load	not supported (98)	87	86	83	6	6	6	6

Remarks:

- 1.) This table shows the currents consumption of the driver at three different operating points (Pmax, Pmid, Pmin) for AC and DC operation.
- 2.) This table is intended for rough design decisions . It is not a replacement for individual functional measurements!