

Manufacturer: OSRAM GmbH Marcel-Breuer Str. 6 D-80807 München	Product: OTi DALI 100/220-240/700 D NFC IND L (4052899559516)	OSRAM GmbH
--	---	-------------------

Table 1

Values for load range	Nominal current of the control gear with connected illuminant in AC-operation		Nominal current of the control gear with connected illuminant in DC- operation (Default output current in emergency mode = 15%)			
	$I_N @ U_N = 230V$ [mA trms]	$I_N @ U_N = 240V$ [mA trms]	$I_N @ U_N = 186V$ [mA trms]	$I_N @ U_N = 216V$ [mA trms]	$I_N @ U_N = 240V$ [mA trms]	$I_N @ U_N = 260V$ [mA trms]
Minimum Load /mA Uout= 120 V Iout= 200 mA P= 24 W	138	135	35	30	28	26
Medium Load /mA Uout= 142 V Iout= 350 mA P= 50 W	248	239	57	49	44	41
Maximum Load /mA Uout= 142 V Iout= 700 mA P= 100 W	477	458	98	85	76	71
Open Load /mA	49	51	12	12	12	12
Short Load /mA	49	51	12	12	12	12

Remarks:

This table shows the currents consumption of the driver at three different operating points (Pmax, Pmed, Pmin) for AC and DC operation.

In DC operation the output current is reduced to 15% light level according to the default parameter setting. This level can be changed via T4T.