

Manufacturer: OSRAM GmbH Marcel-Breuer Str. 6 D-80807 München	Product:  <b>OTi FIT 75/220-240/550 NFC L</b> <b>( 4052899990180 )</b>	<b>OSRAM GmbH</b>
--	---	-------------------

Table 1

Values for load range	AC-operation		DC-Operation			
	AC-operation @ 230V I <sub>in</sub> ( mA )	AC-operation @ 240V I <sub>in</sub> ( mA )	186V I <sub>in</sub> ( mA )	216V I <sub>in</sub> ( mA )	240V I <sub>in</sub> ( mA )	260V I <sub>in</sub> ( mA )
Minimum Load /mA U <sub>out</sub> = 54 V I <sub>out</sub> = 125 mA P= 6,75 W	67	67	54	47	43	41
Mid Load /mA U <sub>out</sub> = 133V I <sub>out</sub> = 264mA P= 35 W	180	174	210	181	163	151
Maximum Load /mA U <sub>out</sub> = 136 V I <sub>out</sub> = 550mA P= 75 W	369	353	447	382	343	317
Short Load	27	27	14	13	14	12
Open Load	27	27	11	11	11	11

Remarks:

This table shows the currents consumption of the driver at three different operating points (P<sub>max</sub>, P<sub>mid</sub>, P<sub>min</sub>) for AC and DC operation.