

DALI magic

Bitte beachten Sie die Sicherheitshinweise im Umgang mit dem Gerät

Allgemeine Informationen

Applikation

PC unabhängig:

- Steuergeräte zum Schalten und Dimmen von DALI Lichtsystemen zum Testen von einzelnen Leuchten oder ganzen Beleuchtungseinrichtungen

Nur in Verbindung mit PC und Software:

- Standard Schnittstelle DALI USB;
 - Zentrale Steuerung, Analyse und Programmierung von DALI Systemen (z.B. Ein- und Auslesen von DALI Gerätekonfigurationen) über die Software „DALI wizard“
 - „DALI-Spy“-Funktionalität zur Protokollierung des Datenflusses auf der DALI Leitung (nur mit Software DALI wizard)

Technische Daten

- Spannungsversorgung via USB: 5V, 60 - 350 mA, integrierter Überspannungsschutz
- Externe Spannungsversorgung: 6V, 1A, Verpolschutz vorhanden
- Externer Versorgungsstecker: DC, EIAJ-03
- USB Anschluss: Type B gem. IEC 61076-3-108

Temperatur und Lebensdauer

- Arbeitsumgebungstemperatur: 0 °C...+50 °C
- Lagertemperatur: -20 °C...+70 °C

Gehäuse

- Abmessungen: 120 mm x 79 mm x 28 mm (B x L x H)
- Gehäusematerial: ABS
- Schutzklasse IP20
- Gewicht: 143 g



DALI wizard und 3DIM Tool: Software Download und Handbuch unter:

https://www.inventronics-light.com/tuner4tronic#software_downloads

© ΕΙΣΑΓΩΓΕΑΣ: Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Forgalmazó: Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Inventronics Poland Sp. z o.o., Al. Jerozolimskie 94, 00-807 Warsaw, Poland
© Inventronics Turkey Teknoloji Ticaret Limited Şirketi, Büyükdere Cad. Bahar Sok. River Plaza No: 13/5 Sisli 34394 Istanbul, Turkey
© Uvoznik: Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Инвентроникс Нидерландия Б.В., Полукстраат 21, 5047 РА Тилбург



IP20

Herstelleradresse:

Inventronics GmbH
Berliner Allee 65
86153 Augsburg
Germany

Technischer Support:
www.inventronicsglobal.com



inventronics

DALI magic

Please observe the safety precautions in handling the device

General information

Application

PC independent:

- Control device for switching and dimming DALI lighting systems for testing of single lights or whole illumination equipments

Only in connection with PC and software:

- Standard interface DALI USB;
 - Central control, analysis and programming of DALI systems (e. g. reading and writing of DALI device configurations) by means of software „DALI wizard“
 - „DALI-Spy“- Functionality for recording data flow on the DALI line by means of software “DALI wizard”

Technical Data

- Power supply via USB: 5V, 60 - 350 mA, integrated overvoltage protection
- External power supply: 6V, 1A, Reverse polarity protected
- External supply plug: DC, EIAJ-03
- USB connection: Type B acc. IEC 61076-3-108

Temperature and lifetime

- Work ambient temperature: 0 °C...+50 °C
- Storage temperature: -20 °C...+70 °C

Housing

- Dimensions: 120 mm x 79 mm x 28 mm (W x L x H)
- Housing material: ABS
- Protection class IP20
- Weight: 143 g



DALI wizard and 3DIM Tool: Software download and manual at:

https://www.inventronics-light.com/tuner4tronic#software_downloads

© Εισαγωγή: Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Forgalmazó: Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Inventronics Poland Sp. z o.o., Al. Jerozolimskie 94, 00-807 Warsaw, Poland
© Inventronics Turkey Teknoloji Ticaret Limited Şirketi, Büyükdere Cad. Bahar Sok. River Plaza No: 13/5 Sisli 34394 Istanbul, Turkey
© Uvoznik: Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Inventronics Netherlands B.V., Polluxstraat 21, 5047RA Tillburg
© Инвентроникс Нидерландия Б.В., Полукстраат 21, 5047 РА Тилбург



IP20

Manufacturer address:

Inventronics GmbH
Berliner Allee 65
86153 Augsburg
Germany

Technical support:

www.inventronicsglobal.com

C10492720
G15129085
03.06.23



inventronics