

# CERTIFICATE

No. U6 120825 0015 Rev. 00

**Holder of Certificate:** Inventronics GmbH

Parkring 31-33  
85748 Garching by Munich  
GERMANY

**Certification Mark:**




**Product:** LED Module

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64142235013101

**Date,** 2023-05-30



( Taylor Yao )

# CERTIFICATE

No. U6 120825 0015 Rev. 00

**Model(s):**

PL-CN50-COB-1400-927-24D-G2;  
PL-CN50-COB-1400-930-24D-G2;  
PL-CN50-COB-1400-935-24D-G2;  
PL-CN50-COB-1400-940-24D-G2;  
PL-CN50-COB-1400-827-24D-G2;  
PL-CN50-COB-1400-830-24D-G2;  
PL-CN50-COB-1400-840-24D-G2;  
PL-CN50-COB-1400-865-24D-G2;  
PL-CN50-COB-1400-927-40D-G2;  
PL-CN50-COB-1400-930-40D-G2;  
PL-CN50-COB-1400-935-40D-G2;  
PL-CN50-COB-1400-940-40D-G2;  
PL-CN50-COB-1400-827-40D-G2;  
PL-CN50-COB-1400-830-40D-G2;  
PL-CN50-COB-1400-840-40D-G2;  
PL-CN50-COB-1400-865-40D-G2;  
PL-CN50-COB-1400-930UW-24D-G2;  
PL-CN50-COB-1400-935UW-24D-G2;  
PL-CN50-COB-1400-930UW-40D-G2;  
PL-CN50-COB-1400-935UW-40D-G2;  
PL-CN50-COB-1400-827-15D-G2;  
PL-CN50-COB-1400-830-15D-G2;  
PL-CN50-COB-1400-840-15D-G2;  
PL-CN50-COB-1400-927-15D-G2;  
PL-CN50-COB-1400-930-15D-G2;  
PL-CN50-COB-1400-935-15D-G2;  
PL-CN50-COB-1400-940-15D-G2

**Brand Name:**

**OSRAM**

# OSRAM

**Parameters:**

Rated Supply Current: 0.35A  
Rated Power: See below table for details  
Method of Installation: Built-in  
Blue Light Risk Group: RG1  
tc: 90°C

# CERTIFICATE

No. U6 120825 0015 Rev. 00

Model No	Rated Power (W)
PL-CN50-COB-1400-927-24D-G2	12.8
PL-CN50-COB-1400-930-24D-G2	
PL-CN50-COB-1400-935-24D-G2	
PL-CN50-COB-1400-940-24D-G2	
PL-CN50-COB-1400-827-24D-G2	
PL-CN50-COB-1400-830-24D-G2	
PL-CN50-COB-1400-840-24D-G2	
PL-CN50-COB-1400-865-24D-G2	
PL-CN50-COB-1400-927-40D-G2	
PL-CN50-COB-1400-930-40D-G2	
PL-CN50-COB-1400-935-40D-G2	
PL-CN50-COB-1400-940-40D-G2	
PL-CN50-COB-1400-827-40D-G2	
PL-CN50-COB-1400-830-40D-G2	
PL-CN50-COB-1400-840-40D-G2	
PL-CN50-COB-1400-865-40D-G2	12.1
PL-CN50-COB-1400-930UW-24D-G2	
PL-CN50-COB-1400-935UW-24D-G2	
PL-CN50-COB-1400-930UW-40D-G2	
PL-CN50-COB-1400-935UW-40D-G2	12.0
PL-CN50-COB-1400-827-15D-G2	
PL-CN50-COB-1400-830-15D-G2	
PL-CN50-COB-1400-840-15D-G2	
PL-CN50-COB-1400-927-15D-G2	
PL-CN50-COB-1400-930-15D-G2	
PL-CN50-COB-1400-935-15D-G2	
PL-CN50-COB-1400-940-15D-G2	

**Tested** EN IEC 62031:2020/A11:2021

**according to:**

**Production** 101562

**Facility(ies):**