



Document number:

2025 / 9C1-4375359-EN-10

---

## 2014/53/EU and amendments

The conformity of the designated product(s) with the provisions of this European Directive is given by the compliance with the following European Standard(s) or other specifications.

If not elsewhere/otherwise indicated the edition/amendment as referenced below applies.

<b>ETSI EN 301 489-3 V2.3.2</b>	ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 3: Specific conditions for Short-Range Devices (SRD) operating on frequencies between 9 kHz and 246 GHz; Harmonised Standard covering the essential requirements of article 3.1(b) of Directive 2014/53/EU
<b>ETSI EN 300 330 V2.1.1</b>	Short Range Devices (SRD) Radio equipment in the frequency range 9 kHz to 25 MHz and inductive loop systems in the frequency range 9 kHz to 30 MHz
<b>EN IEC 55015:2019 + A11:2020</b>	Limits and methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment
<b>EN 61547: 2009</b>	Equipment for general lighting purposes — EMC immunity requirements
<b>EN IEC 61547: 2023</b>	Equipment for general lighting purposes — EMC immunity requirements
<b>EN IEC 61000-3-2:2014</b>	Electromagnetic compatibility (EMC) — Part 3-2: Limits — Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
<b>EN IEC 61000-3-2:2019 +A1:2021</b>	Electromagnetic compatibility (EMC) — Part 3-2: Limits — Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)
<b>EN 61000-3-3:2013</b>	Electromagnetic compatibility (EMC) — Part 3-3: Limits — Limitation of voltage changes, voltage fluctuations and flicker in public low voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subjected to conditional connection
<b>EN 61000-3-3:2013 + A1:2019 +A2:2021</b>	Electromagnetic compatibility (EMC) — Part 3-3: Limits — Limitation of voltage changes, voltage fluctuations and flicker in public low voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subjected to conditional connection
<b>EN 61347-2-13:2014</b>	Lamp controlgear — Part 2-13: Particular requirements for d. c. or a. c. supplied electronic controlgear for LED modules
<b>EN 61347-2-13:2014 + A1:2017</b>	Lamp controlgear — Part 2-13: Particular requirements for d. c. or a. c. supplied electronic controlgear for LED modules
<b>EN 61347-1:2015</b>	Lamp controlgear — Part 1: General and safety requirements
<b>EN 61347-1:2015 + A1:2021</b>	Lamp controlgear — Part 1: General and safety requirements

Document number: 2025 / 9C1-4375359-EN-10

---

## 2009/125/EC and amendments

The conformity of the designated product(s) with the provisions of this European Directive is given by the compliance with the following European Standard(s) or other specifications.

If not elsewhere/otherwise indicated the edition/amendment as referenced below applies.

---

## (EU) 2019/2020 and amendments

The conformity of the designated product(s) with the provisions of this European Directive is given by the compliance with the following European Standard(s) or other specifications.

If not elsewhere/otherwise indicated the edition/amendment as referenced below applies.

**EN IEC 62442-3:2022** Energy performance of lamp controlgear – Part 3: Controlgear for tungsten-halogen lamps and LED light sources – Method of measurement to determine the efficiency of controlgear

---

## 2011/65/EU and amendments

The conformity of the designated product(s) with the provisions of this European Directive is given by the compliance with the following European Standard(s) or other specifications.

If not elsewhere/otherwise indicated the edition/amendment as referenced below applies.

**EN IEC 63000:2018** Technical documentation for the assessment of electrical and electronic products with respect to the restriction of hazardous substances

Document number:

2025 / 9C1-4375359-EN-10

---

**List of models:**

- OT 20/170-240/1A0 1DIM NFC G3 CE
- OT 40/170-240/1A0 1DIM NFC G3 CE
- OT 40/170-240/0A7 1DIM NFC G3 CE
- OT 75/170-240/1A0 1DIM NFC G3 CE
- OT 75/170-240/0A7 1DIM NFC G3 CE
- OT 110/170-240/0A7 1DIM NFC G3 CE
- OT 110/170-240/1A0 1DIM NFC G3 CE
- OT 165/170-240/1A0 1DIM NFC G3 CE
  
- OT 20/170-240/1A0 4DIM NFC G3 CE
- OT 40/170-240/0A7 4DIM NFC G3 CE
- OT 40/170-240/1A0 4DIM NFC G3 CE
- OT 75/170-240/0A7 4DIM NFC G3 CE
- OT 75/170-240/1A0 4DIM NFC G3 CE
- OT 75/170-240/1A5 4DIM NFC G3 CE
- OT 110/170-240/1A0 4DIM NFC G3 CE
- OT 110/170-240/0A7 4DIM NFC G3 CE
- OT 165/170-240/1A0 4DIM NFC G3 CE
- OT 200/170-240/1A0 4DIM NFC G3 CE