

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2340865-0
Report Reference E346592-20230928
Date 5-Oct-2023

Issued to: Inventronics SRL
Via Castagnole 65/A
Treviso, TV 31100
Italy

This is to certify that representative samples of OOQA2 - Light-emitting-diode Arrays - Component
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: UL 8750, Edition 2, Issue Date 2015-09-15, Revision Date 2022-12-07

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.


Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2340865-0
Report Reference E346592-20230928
Date 5-Oct-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model						Category Description
LINEARLight Flex , CFPyyyyInnnn-G1-kxx-24-zz mm, lm/m						Class 2
	Vdc	A/m	W	W/m	m	
100-500		24	0,17	4,00	15,0	
			100			
501-1000	24	0,29	6,90	14,5	100	
1001-1500	24	0,41	9,80	10,2	100	
1501-2000	24	0,51	12,25	8,2		
			100			
2001-2500	24	0,61	14,70	4,6		
			100			
2501-3000	24	0,82	19,60	5,1	100	
3001-3500	24	0,95	22,90	4,4	100	
3501-4000	24	1,09	26,20	3,8	100	
where: yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.						
LINEARLight Flex , CFPyyyyInnnn-G1-kxx-48-zz mm, lm/m						Class 2
	Vdc	A/m	W	W/m	m	
100-500		48	0,08	4,00	25,0	
			100			
501-1000	48	0,14	6,90	14,5	100	
1001-1500	48	0,20	9,80	10,2	100	
1501-2000	48	0,26	12,25	8,2		
			100			
2001-2500	48	0,31	14,70	4,6		
			100			
2501-3000	48	0,41	19,60	5,1		
			100			


 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2340865-0
Report Reference E346592-20230928
Date 5-Oct-2023

<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">3001-3500</td> <td style="width: 10%;">48</td> <td style="width: 10%;">0,48</td> <td style="width: 10%;">23,00</td> <td style="width: 10%;">4,4</td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3501-4000</td> <td>48</td> <td>0,55</td> <td>26,40</td> <td>3,8</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> </table> <p style="text-align: center; margin-top: 10px;">where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>	3001-3500	48	0,48	23,00	4,4				100				3501-4000	48	0,55	26,40	3,8				100																																																				
3001-3500	48	0,48	23,00	4,4																																																																					
		100																																																																							
3501-4000	48	0,55	26,40	3,8																																																																					
		100																																																																							
<p>LINEARLight Flex, CFyyyyInnnn-G1-kxx-24-zz mm,</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">lm/m</th> <th style="width: 10%;">Vdc</th> <th style="width: 10%;">A/m</th> <th style="width: 10%;">W</th> <th style="width: 10%;">W/m</th> <th style="width: 10%;">m</th> </tr> </thead> <tbody> <tr> <td>100-500</td> <td></td> <td>24</td> <td style="text-align: center;">100</td> <td>0,17</td> <td>4,00 15,0</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>24</td> <td>0,29</td> <td>6,90</td> <td>14,5</td> <td>100</td> </tr> <tr> <td>1001-1500</td> <td>24</td> <td>0,41</td> <td>9,80</td> <td>10,2</td> <td>100</td> </tr> <tr> <td>1501-2000</td> <td>24</td> <td>0,51</td> <td>12,25</td> <td>8,2</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>24</td> <td>0,61</td> <td>14,70</td> <td>4,6</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2501-3000</td> <td>24</td> <td>0,82</td> <td>19,60</td> <td>5,1</td> <td>100</td> </tr> <tr> <td>3001-3500</td> <td>24</td> <td>0,95</td> <td>22,90</td> <td>4,4</td> <td>100</td> </tr> <tr> <td>3501-4000</td> <td>24</td> <td>1,09</td> <td>26,20</td> <td>3,8</td> <td>100</td> </tr> </tbody> </table> <p style="text-align: center; margin-top: 10px;">where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>	lm/m	Vdc	A/m	W	W/m	m	100-500		24	100	0,17	4,00 15,0				100			501-1000	24	0,29	6,90	14,5	100	1001-1500	24	0,41	9,80	10,2	100	1501-2000	24	0,51	12,25	8,2				100				2001-2500	24	0,61	14,70	4,6				100				2501-3000	24	0,82	19,60	5,1	100	3001-3500	24	0,95	22,90	4,4	100	3501-4000	24	1,09	26,20	3,8	100	Class 2
lm/m	Vdc	A/m	W	W/m	m																																																																				
100-500		24	100	0,17	4,00 15,0																																																																				
			100																																																																						
501-1000	24	0,29	6,90	14,5	100																																																																				
1001-1500	24	0,41	9,80	10,2	100																																																																				
1501-2000	24	0,51	12,25	8,2																																																																					
		100																																																																							
2001-2500	24	0,61	14,70	4,6																																																																					
		100																																																																							
2501-3000	24	0,82	19,60	5,1	100																																																																				
3001-3500	24	0,95	22,90	4,4	100																																																																				
3501-4000	24	1,09	26,20	3,8	100																																																																				
<p>LINEARLight Flex, CFyyyyInnnn-G1-kxx-48-zz mm,</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">lm/m</th> <th style="width: 10%;">Vdc</th> <th style="width: 10%;">A/m</th> <th style="width: 10%;">W</th> <th style="width: 10%;">W/m</th> <th style="width: 10%;">m</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> </tr> </tbody> </table>	lm/m	Vdc	A/m	W	W/m	m				100			Class 2																																																												
lm/m	Vdc	A/m	W	W/m	m																																																																				
			100																																																																						

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



9C1 4511753-EN-00 #RL-Released 2023-10-06 #Confirm valid copy #LAB #ULC-E11Certif Flex Infinite # #717 #NICO.TONUSSI #OSRAM 0LQ(V)

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2340865-0
Report Reference E346592-20230928
Date 5-Oct-2023

100-500	48	0,08	4,00	25,0	
		100			
501-1000	48	0,14	6,90	14,5	100
1001-1500	48	0,20	9,80	10,2	100
1501-2000	48	0,26	12,25	8,2	
		100			
2001-2500	48	0,31	14,70	4,6	
		100			
2501-3000	48	0,41	19,60	5,1	
		100			
3001-3500	48	0,48	23,00	4,4	
		100			
3501-4000	48	0,55	26,40	3,8	
		100			
<p>where: yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>					
<p>LINEARLight Flex, LFPyyyyl-G1-kxx-24-zz mm, lm/m</p> <p>Vdc A/m W/m m</p>					Class 2
		W			
100-500		24	0,17	4,00	15,0
		100			
501-1000	24	0,29	6,90	14,5	100
1001-1500	24	0,41	9,80	10,2	100
1501-2000	24	0,51	12,25	8,2	
		100			
2001-2500	24	0,61	14,70	4,6	
		100			
2501-3000	24	0,82	19,60	5,1	100
3001-3500	24	0,95	22,90	4,4	100
3501-4000	24	1,09	26,20	3,8	100
<p>where: yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT,</p>					



Deborah Jennings-Conner
 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

9C1 4511753-EN-00 #RL-Released 2023-10-06 #Confirm valid copy #LAB #ULC-E11Certif Flex Infinite # #717 #NICO.TONUSSI #OSRAM 0LQ(V)

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2340865-0
Report Reference E346592-20230928
Date 5-Oct-2023

zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.																																																																												
<p>LINEARLight Flex, LFPyyyyl-G1-kxx-48-zz mm, lm/m</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Vdc</th> <th style="text-align: left;">A/m</th> <th style="text-align: left;">W</th> <th style="text-align: left;">W/m</th> <th style="text-align: left;">m</th> </tr> </thead> <tbody> <tr> <td>100-500</td> <td>48</td> <td>0,08</td> <td>4,00</td> <td>25,0</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>48</td> <td>0,14</td> <td>6,90</td> <td>14,5</td> </tr> <tr> <td>1001-1500</td> <td>48</td> <td>0,20</td> <td>9,80</td> <td>10,2</td> </tr> <tr> <td>1501-2000</td> <td>48</td> <td>0,26</td> <td>12,25</td> <td>8,2</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>48</td> <td>0,31</td> <td>14,70</td> <td>4,6</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2501-3000</td> <td>48</td> <td>0,41</td> <td>19,60</td> <td>5,1</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>3001-3500</td> <td>48</td> <td>0,48</td> <td>23,00</td> <td>4,4</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>3501-4000</td> <td>48</td> <td>0,55</td> <td>26,40</td> <td>3,8</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> </tbody> </table> <p style="text-align: center;">where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>	Vdc	A/m	W	W/m	m	100-500	48	0,08	4,00	25,0			100			501-1000	48	0,14	6,90	14,5	1001-1500	48	0,20	9,80	10,2	1501-2000	48	0,26	12,25	8,2			100			2001-2500	48	0,31	14,70	4,6			100			2501-3000	48	0,41	19,60	5,1			100			3001-3500	48	0,48	23,00	4,4			100			3501-4000	48	0,55	26,40	3,8			100			Class 2
Vdc	A/m	W	W/m	m																																																																								
100-500	48	0,08	4,00	25,0																																																																								
		100																																																																										
501-1000	48	0,14	6,90	14,5																																																																								
1001-1500	48	0,20	9,80	10,2																																																																								
1501-2000	48	0,26	12,25	8,2																																																																								
		100																																																																										
2001-2500	48	0,31	14,70	4,6																																																																								
		100																																																																										
2501-3000	48	0,41	19,60	5,1																																																																								
		100																																																																										
3001-3500	48	0,48	23,00	4,4																																																																								
		100																																																																										
3501-4000	48	0,55	26,40	3,8																																																																								
		100																																																																										
<p>LINEARLight Flex, LFyyyyl-G1-kxx-24-zz mm, lm/m</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Vdc</th> <th style="text-align: left;">A/m</th> <th style="text-align: left;">W</th> <th style="text-align: left;">W/m</th> <th style="text-align: left;">m</th> </tr> </thead> <tbody> <tr> <td>100-500</td> <td>24</td> <td>0,17</td> <td>4,00</td> <td>15,0</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>24</td> <td>0,29</td> <td>6,90</td> <td>14,5</td> </tr> <tr> <td>1001-1500</td> <td>24</td> <td>0,41</td> <td>9,80</td> <td>10,2</td> </tr> <tr> <td>1501-2000</td> <td>24</td> <td>0,51</td> <td>12,25</td> <td>8,2</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>24</td> <td>0,61</td> <td>14,70</td> <td>4,6</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> </tbody> </table>	Vdc	A/m	W	W/m	m	100-500	24	0,17	4,00	15,0			100			501-1000	24	0,29	6,90	14,5	1001-1500	24	0,41	9,80	10,2	1501-2000	24	0,51	12,25	8,2			100			2001-2500	24	0,61	14,70	4,6			100			Class 2																														
Vdc	A/m	W	W/m	m																																																																								
100-500	24	0,17	4,00	15,0																																																																								
		100																																																																										
501-1000	24	0,29	6,90	14,5																																																																								
1001-1500	24	0,41	9,80	10,2																																																																								
1501-2000	24	0,51	12,25	8,2																																																																								
		100																																																																										
2001-2500	24	0,61	14,70	4,6																																																																								
		100																																																																										



Deborah Jennings-Conner, VP Regulatory Services

UL LLC
 Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

#717 #NICO.TONUSSI #OSRAM 0LQ(V) # #ULC-E11Certif Flex Infinite #LAB #ULC-E11Certif Flex Infinite #Confirm valid copy #2023-10-06 #RL-Releasd #9C1 4511753-EN-00

CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-2340865-0
Report Reference E346592-20230928
Date 5-Oct-2023

2501-3000	24	0,82	19,60	5,1	100	
3001-3500	24	0,95	22,90	4,4	100	
3501-4000	24	1,09	26,20	3,8	100	
<p>where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>						
<p>LINEARLight Flex, LFyyyyl-G1-kxx-48-zz mm, lm/m</p> <p>Vdc A/m W/m m</p>						Class 2
100-500		48	0,08	4,00	25,0	
			100			
501-1000	48	0,14	6,90	14,5	100	
1001-1500	48	0,20	9,80	10,2	100	
1501-2000	48	0,26	12,25	8,2		
			100			
2001-2500	48	0,31	14,70	4,6		
			100			
2501-3000	48	0,41	19,60	5,1		
			100			
3001-3500	48	0,48	23,00	4,4		
			100			
3501-4000	48	0,55	26,40	3,8		
			100			
<p>where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>						


 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2335314-0
Report Reference E346592-20230928
Date 5-Oct-2023

Issued to: Inventronics SRL
Via Castagnole 65/A
Treviso, TV 31100
Italy

**This is to certify that
representative samples of**

OOQA8 - Light-emitting-diode Arrays Certified for Canada -
Component

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the component requirements in the Standard(s) indicated on this Certificate. UL Recognized components are incomplete in certain constructional features or restricted in performance capabilities and are intended for installation in complete equipment submitted for investigation to UL LLC.

Standard(s) for Safety: CSA C22.2 No. 250.13, Edition 5, Issue Date 2022-05

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Recognized Component Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Recognized Component Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Recognized Component Mark on the product.


Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2335314-0
Report Reference E346592-20230928
Date 5-Oct-2023

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model						Category Description
LINEARLight Flex , CFPyyyyInnnn-G1-kxx-24-zz mm, lm/m						Class 2
	Vdc	A/m	W	W/m	m	
100-500		24	0,17	4,00	15,0	
			100			
501-1000	24	0,29	6,90	14,5	100	
1001-1500	24	0,41	9,80	10,2	100	
1501-2000	24	0,51	12,25	8,2		
			100			
2001-2500	24	0,61	14,70	4,6		
			100			
2501-3000	24	0,82	19,60	5,1	100	
3001-3500	24	0,95	22,90	4,4	100	
3501-4000	24	1,09	26,20	3,8	100	
where: yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.						
LINEARLight Flex , CFPyyyyInnnn-G1-kxx-48-zz mm, lm/m						Class 2
	Vdc	A/m	W	W/m	m	
100-500		48	0,08	4,00	25,0	
			100			
501-1000	48	0,14	6,90	14,5	100	
1001-1500	48	0,20	9,80	10,2	100	
1501-2000	48	0,26	12,25	8,2		
			100			
2001-2500	48	0,31	14,70	4,6		
			100			
2501-3000	48	0,41	19,60	5,1		
			100			


 Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2335314-0
Report Reference E346592-20230928
Date 5-Oct-2023

<table style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 15%;">3001-3500</td> <td style="width: 10%;">48</td> <td style="width: 10%;">0,48</td> <td style="width: 10%;">23,00</td> <td style="width: 10%;">4,4</td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3501-4000</td> <td>48</td> <td>0,55</td> <td>26,40</td> <td>3,8</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> </table> <p style="text-align: center; margin-top: 10px;">where:</p> <p> yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides. </p>	3001-3500	48	0,48	23,00	4,4				100				3501-4000	48	0,55	26,40	3,8				100																																																				
3001-3500	48	0,48	23,00	4,4																																																																					
		100																																																																							
3501-4000	48	0,55	26,40	3,8																																																																					
		100																																																																							
<p>LINEARLight Flex, CFyyyyInnnn-G1-kxx-24-zz mm,</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">lm/m</th> <th style="width: 10%;">Vdc</th> <th style="width: 10%;">A/m</th> <th style="width: 10%;">W</th> <th style="width: 10%;">W/m</th> <th style="width: 10%;">m</th> </tr> </thead> <tbody> <tr> <td>100-500</td> <td></td> <td>24</td> <td>0,17</td> <td>4,00</td> <td>15,0</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>24</td> <td>0,29</td> <td>6,90</td> <td>14,5</td> <td>100</td> </tr> <tr> <td>1001-1500</td> <td>24</td> <td>0,41</td> <td>9,80</td> <td>10,2</td> <td>100</td> </tr> <tr> <td>1501-2000</td> <td>24</td> <td>0,51</td> <td>12,25</td> <td>8,2</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>24</td> <td>0,61</td> <td>14,70</td> <td>4,6</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> </tr> <tr> <td>2501-3000</td> <td>24</td> <td>0,82</td> <td>19,60</td> <td>5,1</td> <td>100</td> </tr> <tr> <td>3001-3500</td> <td>24</td> <td>0,95</td> <td>22,90</td> <td>4,4</td> <td>100</td> </tr> <tr> <td>3501-4000</td> <td>24</td> <td>1,09</td> <td>26,20</td> <td>3,8</td> <td>100</td> </tr> </tbody> </table> <p style="text-align: center; margin-top: 10px;">where:</p> <p> yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides. </p>	lm/m	Vdc	A/m	W	W/m	m	100-500		24	0,17	4,00	15,0				100			501-1000	24	0,29	6,90	14,5	100	1001-1500	24	0,41	9,80	10,2	100	1501-2000	24	0,51	12,25	8,2					100			2001-2500	24	0,61	14,70	4,6					100			2501-3000	24	0,82	19,60	5,1	100	3001-3500	24	0,95	22,90	4,4	100	3501-4000	24	1,09	26,20	3,8	100	Class 2
lm/m	Vdc	A/m	W	W/m	m																																																																				
100-500		24	0,17	4,00	15,0																																																																				
			100																																																																						
501-1000	24	0,29	6,90	14,5	100																																																																				
1001-1500	24	0,41	9,80	10,2	100																																																																				
1501-2000	24	0,51	12,25	8,2																																																																					
			100																																																																						
2001-2500	24	0,61	14,70	4,6																																																																					
			100																																																																						
2501-3000	24	0,82	19,60	5,1	100																																																																				
3001-3500	24	0,95	22,90	4,4	100																																																																				
3501-4000	24	1,09	26,20	3,8	100																																																																				
<p>LINEARLight Flex, CFyyyyInnnn-G1-kxx-48-zz mm,</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">lm/m</th> <th style="width: 10%;">Vdc</th> <th style="width: 10%;">A/m</th> <th style="width: 10%;">W</th> <th style="width: 10%;">W/m</th> <th style="width: 10%;">m</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">W</td> <td></td> <td></td> </tr> </tbody> </table>	lm/m	Vdc	A/m	W	W/m	m				W			Class 2																																																												
lm/m	Vdc	A/m	W	W/m	m																																																																				
			W																																																																						

Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



9C1 4511753-EN-00 #RL-Released 2023-10-06 #Confirm valid copy #LAB #ULC-E11Certif Flex Infinite # #717 #NICO.TONUSSI #OSRAM 0LQ(V)

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2335314-0
Report Reference E346592-20230928
Date 5-Oct-2023

<table style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="width: 20%;">100-500</td> <td style="width: 10%;">48</td> <td style="width: 10%;">0,08</td> <td style="width: 10%;">4,00</td> <td style="width: 10%;">25,0</td> <td style="width: 10%;"></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>48</td> <td>0,14</td> <td>6,90</td> <td>14,5</td> <td>100</td> </tr> <tr> <td>1001-1500</td> <td>48</td> <td>0,20</td> <td>9,80</td> <td>10,2</td> <td>100</td> </tr> <tr> <td>1501-2000</td> <td>48</td> <td>0,26</td> <td>12,25</td> <td>8,2</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>48</td> <td>0,31</td> <td>14,70</td> <td>4,6</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2501-3000</td> <td>48</td> <td>0,41</td> <td>19,60</td> <td>5,1</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3001-3500</td> <td>48</td> <td>0,48</td> <td>23,00</td> <td>4,4</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3501-4000</td> <td>48</td> <td>0,55</td> <td>26,40</td> <td>3,8</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> </tbody> </table> <p style="text-align: center; margin-top: 20px;">where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>	100-500	48	0,08	4,00	25,0				100				501-1000	48	0,14	6,90	14,5	100	1001-1500	48	0,20	9,80	10,2	100	1501-2000	48	0,26	12,25	8,2				100				2001-2500	48	0,31	14,70	4,6				100				2501-3000	48	0,41	19,60	5,1				100				3001-3500	48	0,48	23,00	4,4				100				3501-4000	48	0,55	26,40	3,8				100				<p>Class 2</p>
100-500	48	0,08	4,00	25,0																																																																																	
		100																																																																																			
501-1000	48	0,14	6,90	14,5	100																																																																																
1001-1500	48	0,20	9,80	10,2	100																																																																																
1501-2000	48	0,26	12,25	8,2																																																																																	
		100																																																																																			
2001-2500	48	0,31	14,70	4,6																																																																																	
		100																																																																																			
2501-3000	48	0,41	19,60	5,1																																																																																	
		100																																																																																			
3001-3500	48	0,48	23,00	4,4																																																																																	
		100																																																																																			
3501-4000	48	0,55	26,40	3,8																																																																																	
		100																																																																																			
<p>LINEARLight Flex, LFPyyyyl-G1-kxx-24-zz mm, lm/m</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 20%;"></th> <th style="width: 10%;">Vdc</th> <th style="width: 10%;">A/m</th> <th style="width: 10%;">W/m</th> <th style="width: 10%;">m</th> <th style="width: 10%;"></th> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">W</td> <td></td> <td></td> </tr> </thead> <tbody> <tr> <td>100-500</td> <td></td> <td>24</td> <td>0,17</td> <td>4,00</td> <td>15,0</td> </tr> <tr> <td></td> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>24</td> <td>0,29</td> <td>6,90</td> <td>14,5</td> <td>100</td> </tr> <tr> <td>1001-1500</td> <td>24</td> <td>0,41</td> <td>9,80</td> <td>10,2</td> <td>100</td> </tr> <tr> <td>1501-2000</td> <td>24</td> <td>0,51</td> <td>12,25</td> <td>8,2</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>24</td> <td>0,61</td> <td>14,70</td> <td>4,6</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">100</td> <td></td> <td></td> <td></td> </tr> <tr> <td>2501-3000</td> <td>24</td> <td>0,82</td> <td>19,60</td> <td>5,1</td> <td>100</td> </tr> <tr> <td>3001-3500</td> <td>24</td> <td>0,95</td> <td>22,90</td> <td>4,4</td> <td>100</td> </tr> <tr> <td>3501-4000</td> <td>24</td> <td>1,09</td> <td>26,20</td> <td>3,8</td> <td>100</td> </tr> </tbody> </table> <p style="text-align: center; margin-top: 20px;">where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT,</p>		Vdc	A/m	W/m	m					W			100-500		24	0,17	4,00	15,0				100			501-1000	24	0,29	6,90	14,5	100	1001-1500	24	0,41	9,80	10,2	100	1501-2000	24	0,51	12,25	8,2				100				2001-2500	24	0,61	14,70	4,6				100				2501-3000	24	0,82	19,60	5,1	100	3001-3500	24	0,95	22,90	4,4	100	3501-4000	24	1,09	26,20	3,8	100							
	Vdc	A/m	W/m	m																																																																																	
			W																																																																																		
100-500		24	0,17	4,00	15,0																																																																																
			100																																																																																		
501-1000	24	0,29	6,90	14,5	100																																																																																
1001-1500	24	0,41	9,80	10,2	100																																																																																
1501-2000	24	0,51	12,25	8,2																																																																																	
		100																																																																																			
2001-2500	24	0,61	14,70	4,6																																																																																	
		100																																																																																			
2501-3000	24	0,82	19,60	5,1	100																																																																																
3001-3500	24	0,95	22,90	4,4	100																																																																																
3501-4000	24	1,09	26,20	3,8	100																																																																																



Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

9C1 4511753-EN-00 #RL-Released 2023-10-06 #Confirm valid copy #LAB #ULC-E11Certif Flex Infinite # #717 #NICO.TONUSSI #OSRAM 0LQ(V)

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2335314-0
Report Reference E346592-20230928
Date 5-Oct-2023

zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.																																																																												
<p>LINEARLight Flex, LFPyyyyl-G1-kxx-48-zz mm, lm/m</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Vdc</th> <th style="text-align: left;">A/m</th> <th style="text-align: left;">W</th> <th style="text-align: left;">W/m</th> <th style="text-align: left;">m</th> </tr> </thead> <tbody> <tr> <td>100-500</td> <td>48</td> <td>0,08</td> <td>4,00</td> <td>25,0</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>48</td> <td>0,14</td> <td>6,90</td> <td>14,5</td> </tr> <tr> <td>1001-1500</td> <td>48</td> <td>0,20</td> <td>9,80</td> <td>10,2</td> </tr> <tr> <td>1501-2000</td> <td>48</td> <td>0,26</td> <td>12,25</td> <td>8,2</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>48</td> <td>0,31</td> <td>14,70</td> <td>4,6</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2501-3000</td> <td>48</td> <td>0,41</td> <td>19,60</td> <td>5,1</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>3001-3500</td> <td>48</td> <td>0,48</td> <td>23,00</td> <td>4,4</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>3501-4000</td> <td>48</td> <td>0,55</td> <td>26,40</td> <td>3,8</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> </tbody> </table> <p style="text-align: center;">where:</p> <p>yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides.</p>	Vdc	A/m	W	W/m	m	100-500	48	0,08	4,00	25,0			100			501-1000	48	0,14	6,90	14,5	1001-1500	48	0,20	9,80	10,2	1501-2000	48	0,26	12,25	8,2			100			2001-2500	48	0,31	14,70	4,6			100			2501-3000	48	0,41	19,60	5,1			100			3001-3500	48	0,48	23,00	4,4			100			3501-4000	48	0,55	26,40	3,8			100			Class 2
Vdc	A/m	W	W/m	m																																																																								
100-500	48	0,08	4,00	25,0																																																																								
		100																																																																										
501-1000	48	0,14	6,90	14,5																																																																								
1001-1500	48	0,20	9,80	10,2																																																																								
1501-2000	48	0,26	12,25	8,2																																																																								
		100																																																																										
2001-2500	48	0,31	14,70	4,6																																																																								
		100																																																																										
2501-3000	48	0,41	19,60	5,1																																																																								
		100																																																																										
3001-3500	48	0,48	23,00	4,4																																																																								
		100																																																																										
3501-4000	48	0,55	26,40	3,8																																																																								
		100																																																																										
<p>LINEARLight Flex, LFyyyyl-G1-kxx-24-zz mm, lm/m</p> <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;">Vdc</th> <th style="text-align: left;">A/m</th> <th style="text-align: left;">W</th> <th style="text-align: left;">W/m</th> <th style="text-align: left;">m</th> </tr> </thead> <tbody> <tr> <td>100-500</td> <td>24</td> <td>0,17</td> <td>4,00</td> <td>15,0</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>24</td> <td>0,29</td> <td>6,90</td> <td>14,5</td> </tr> <tr> <td>1001-1500</td> <td>24</td> <td>0,41</td> <td>9,80</td> <td>10,2</td> </tr> <tr> <td>1501-2000</td> <td>24</td> <td>0,51</td> <td>12,25</td> <td>8,2</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>24</td> <td>0,61</td> <td>14,70</td> <td>4,6</td> </tr> <tr> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> </tbody> </table>	Vdc	A/m	W	W/m	m	100-500	24	0,17	4,00	15,0			100			501-1000	24	0,29	6,90	14,5	1001-1500	24	0,41	9,80	10,2	1501-2000	24	0,51	12,25	8,2			100			2001-2500	24	0,61	14,70	4,6			100			Class 2																														
Vdc	A/m	W	W/m	m																																																																								
100-500	24	0,17	4,00	15,0																																																																								
		100																																																																										
501-1000	24	0,29	6,90	14,5																																																																								
1001-1500	24	0,41	9,80	10,2																																																																								
1501-2000	24	0,51	12,25	8,2																																																																								
		100																																																																										
2001-2500	24	0,61	14,70	4,6																																																																								
		100																																																																										



Deborah Jennings-Conner, VP Regulatory Services

 UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

9C1 4511753-EN-00 #RL-Released 2023-10-06 #Confirm valid copy #LAB #ULC-E11Certif Flex Infinite # #717 #NICO.TONUSSI #OSRAM 0LQ(V

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-2335314-0
Report Reference E346592-20230928
Date 5-Oct-2023

<table> <tr> <td>2501-3000</td> <td>24</td> <td>0,82</td> <td>19,60</td> <td>5,1</td> <td>100</td> </tr> <tr> <td>3001-3500</td> <td>24</td> <td>0,95</td> <td>22,90</td> <td>4,4</td> <td>100</td> </tr> <tr> <td>3501-4000</td> <td>24</td> <td>1,09</td> <td>26,20</td> <td>3,8</td> <td>100</td> </tr> </table> <p> where: yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides. </p>	2501-3000	24	0,82	19,60	5,1	100	3001-3500	24	0,95	22,90	4,4	100	3501-4000	24	1,09	26,20	3,8	100																																																																															
2501-3000	24	0,82	19,60	5,1	100																																																																																												
3001-3500	24	0,95	22,90	4,4	100																																																																																												
3501-4000	24	1,09	26,20	3,8	100																																																																																												
<p>LINEARlight Flex, LFyyyyl-G1-kxx-48-zz mm, lm/m</p> <table> <thead> <tr> <th></th> <th>Vdc</th> <th>A/m</th> <th>W/m</th> <th>m</th> <th></th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> <td>W</td> <td></td> <td></td> </tr> <tr> <td>100-500</td> <td></td> <td>48</td> <td>0,08</td> <td>4,00</td> <td>25,0</td> </tr> <tr> <td></td> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>501-1000</td> <td>48</td> <td>0,14</td> <td>6,90</td> <td>14,5</td> <td>100</td> </tr> <tr> <td>1001-1500</td> <td>48</td> <td>0,20</td> <td>9,80</td> <td>10,2</td> <td>100</td> </tr> <tr> <td>1501-2000</td> <td>48</td> <td>0,26</td> <td>12,25</td> <td>8,2</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2001-2500</td> <td>48</td> <td>0,31</td> <td>14,70</td> <td>4,6</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>2501-3000</td> <td>48</td> <td>0,41</td> <td>19,60</td> <td>5,1</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>3001-3500</td> <td>48</td> <td>0,48</td> <td>23,00</td> <td>4,4</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> <tr> <td>3501-4000</td> <td>48</td> <td>0,55</td> <td>26,40</td> <td>3,8</td> <td></td> </tr> <tr> <td></td> <td></td> <td></td> <td>100</td> <td></td> <td></td> </tr> </tbody> </table> <p> where: yyyy: reference luminous flux [lumen/m], nnnn: empty or any customer identification code, k: 8 or 9, first digit of CRI, xx: from 20 to 80, first 2 digits of CCT, zz: LED module length (m), according to the max length, mm: blank, C with terminal, L1(or 1L) with tails from one side, L2(or 2L) with tails from both sides. </p>		Vdc	A/m	W/m	m					W			100-500		48	0,08	4,00	25,0				100			501-1000	48	0,14	6,90	14,5	100	1001-1500	48	0,20	9,80	10,2	100	1501-2000	48	0,26	12,25	8,2					100			2001-2500	48	0,31	14,70	4,6					100			2501-3000	48	0,41	19,60	5,1					100			3001-3500	48	0,48	23,00	4,4					100			3501-4000	48	0,55	26,40	3,8					100			Class 2
	Vdc	A/m	W/m	m																																																																																													
			W																																																																																														
100-500		48	0,08	4,00	25,0																																																																																												
			100																																																																																														
501-1000	48	0,14	6,90	14,5	100																																																																																												
1001-1500	48	0,20	9,80	10,2	100																																																																																												
1501-2000	48	0,26	12,25	8,2																																																																																													
			100																																																																																														
2001-2500	48	0,31	14,70	4,6																																																																																													
			100																																																																																														
2501-3000	48	0,41	19,60	5,1																																																																																													
			100																																																																																														
3001-3500	48	0,48	23,00	4,4																																																																																													
			100																																																																																														
3501-4000	48	0,55	26,40	3,8																																																																																													
			100																																																																																														


 Deborah Jennings-Conner, VP Regulatory Services
 UL LLC



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

9C1 4511753-EN-00 #RL-Released 2023-10-06 #Confirm valid copy #LAB #ULC-E11Certif Flex Infinite # #717 #NICO.TONUSSI #OSRAM 0LQ(V