



Product Service

Attestation of Conformity

No. N8A 18 01 84117 055

Holder of Certificate: Osram GmbH

Marcel-Breuer-Str. 6

80807 München

GERMANY

**Product: Electronic controlgear for LED modules
(24V Constant Voltage LED Power Supply)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. See also notes overleaf.

Test report no.: 64140170524201**Date,** 2018-01-17

(Michael Xu)



After preparation of the necessary technical documentation as well as the EU conformity declaration the required CE marking can be affixed on the product. That declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.

Page 1 of 2



Product Service

Attestation of Conformity
No. N8A 18 01 84117 055

Model(s): OT 20/220-240/24 DIM P, OT 20/220-240/24 P,
 OT 40/220-240/24 DIM P, OT 40/220-240/24 P,
 OT 60/220-240/24 DIM P, OT 60/220-240/24 P

Brand: OSRAM

Parameters:

Rated Input:	220-240VAC, 50/60Hz or 176-250VDC
Protection against Electric Shock:	Class II; SELV
Degree of Protection:	IP66
Method of Installation:	Independent
Type of Output:	Constant voltage type
ta:	-30~50°C (OT 60/220-240/24 DIM P, OT 60/220-240/24 P); -30~55°C (other models)
tc:	85°C (OT 20/220-240/24 DIM P, OT 20/220-240/24 P); 90°C (other models)
Rated Output Voltage:	24VDC
Max. Output Voltage:	30VDC

Model	Rated max. output current (mA)
OT 20/220-240/24 DIM P	830
OT 20/220-240/24 P	830
OT 40/220-240/24 DIM P	1670
OT 40/220-240/24 P	1670
OT 60/220-240/24 DIM P	2500
OT 60/220-240/24 P	2500

Model	Rated Max. output power (W)
OT 20/220-240/24 DIM P	20
OT 20/220-240/24 P	20
OT 40/220-240/24 DIM P	40
OT 40/220-240/24 P	40
OT 60/220-240/24 DIM P	60
OT 60/220-240/24 P	60

Tested according to: EN 61347-1:2015
 EN 61347-2-13:2014/A1:2017
 EN 62493:2015